



## HAMPTON LVT PLANK

<b>Classification</b>	ASTM F 1700-04 Class III, type B Solid Vinyl Floor Tile	
<b>Size</b>	36.85"x5.91" (936mm x 150mm)	
<b>Overall Thickness</b>	4.2mm	
<b>Wearlayer Thickness</b>	20mil (0.5mm)	
<b>Construction</b>	Layered Plank consisting of wearlayer, film, and backing.	
<b>Edge</b>	Micro beveled	
<b>Limited Wear Warranty</b>	Lifetime Residential / 10 year commercial	
<b>Recycled Content</b>	This product contains up to 20% recycled content.	
<b>Packaging</b>	18.14 Sqft (1.68 sqm) per carton	
	12 Planks per carton	
	66 cartons per pallet	
	20 pallets per 20' container	
<b>Weight per Carton</b>	30.1 lbs. (13.68 kg.)	
<b>Product Testing</b>		
<b>Flammability</b>	ASTM D 2859-06/CPSC FF 1-70	Passed
<b>Critical Radiant Flux</b>	ASTM E 648-06	Class I, CRF $\geq$ 0.45
<b>Smoke Density</b>	ASTM E 662-06	< 450
<b>Slip Resistance</b>	ASTM C 1028	Exceeds ADA and OSHA Recommendations
<b>Static Load Limit</b>	ASTM F 970	1500 psi



## HAMPTON LVT PLANK

<b>Classification</b>	ASTM F 1700-04 Class III, type B Solid Vinyl Floor Tile	
<b>Size</b>	36"X6" (914.40mm x 152.40mm)	
<b>Overall Thickness</b>	2mm	
<b>Wearlayer Thickness</b>	12mil (0.3mm)	
<b>Construction</b>	Layered Plank consisting of wearlayer, film, and backing.	
<b>Edge</b>	Square	
<b>Limited Wear Warranty</b>	40 Year Residential / 7 Year Commercial	
<b>Recycled Content</b>	This product contains up to 20% recycled content.	
<b>Packaging</b>	36.00 Sqft (3.34 sqm) per carton	
	24 Planks per carton	
	70 cartons per pallet	
	20 pallets per 20' container	
<b>Weight per Carton</b>	29.50 lbs. (13.38 kg.)	
<b>Product Testing</b>		
<b>Flammability</b>	ASTM D 2859-06/CPSC FF 1-70	Passed
<b>Critical Radiant Flux</b>	ASTM E 648-06	Class I, CRF $\geq$ 0.45
<b>Smoke Density</b>	ASTM E 662-06	< 450
<b>Slip Resistance</b>	ASTM C 1028	Exceeds ADA and OSHA Recommendations
<b>Static Load Limit</b>	ASTM F 970	1500 psi